


• YOUR
• SMART
• ENERGY



SMILE-SP/SPB SERIES

7.6 kW 8.2 kWh / 9.6 kW 8.2 kWh

Expandable to **49.2 kWh** with
8.2 kWh Battery Module



Outdoor

24/7 Monitoring

AFCI & Rapid Shutdown

4 MPPTs

High Efficiency Battery

WIFI Module Integrated

SMILE-SP/SPB SERIES



Model	SMILE-SP7.6	SMILE-SP9.6	SMILE-SPB7.6	SMILE-SPB9.6
Inverter PV Data				
Max. PV Input Power	11.4 kW	15 kW	N.A	N.A
Max. PV Input Voltage	600 V	600 V	N.A	N.A
MPPT Operating Voltage Range	80 ~ 550 V	80 ~ 550 V	N.A	N.A
Start-up Voltage	95 V	95 V	N.A	N.A
Number of MPPTs	4	4	N.A	N.A
Max. Input Current per MPPT	12.5 A	12.5 A	N.A	N.A
Max. Short Circuit Current per MPPT	15.2 A	15.2 A	N.A	N.A
Inverter AC Input and Output Data				
Nominal AC Output Power	7.6 kW	9.6 kW	7.6 kW	9.6 kW
Max. Apparent Power Output to Grid	7.6 kVA	9.6 kVA	7.6 kVA	9.6 kVA
Nominal AC Input Power	9.12 kW	9.6 kW	9.12 kW	9.6 kW
Max. Apparent Power from Grid	9.12 kVA	9.6 kVA	9.12 kVA	9.6 kVA
Output Voltage Range	211 to 264 Vac @240 Vac			
Nominal AC Grid Frequency	60 Hz	60 Hz	60 Hz	60 Hz
Max. AC Current Output to Utility Grid	31.7 A	40 A	31.7 A	40 A
Max. AC Current From Utility Grid	38 A	40 A	38 A	40 A
Power Factor	~1 (Adjustable from 0.8 leading to 0.8 lagging)			
Max. Total Harmonic Distortion	<3%	<3%	<3%	<3%
Inverter Backup Data				
Max. Output Apparent Power@240V	7.6 kVA	9.6 kVA	7.6 kVA	9.6 kVA
Peak Output Apparent Power@240V	9.12 kVA@60sec	11.52 kVA@60sec	9.12 kVA@60sec	11.52 kVA@60sec
Max. Output Current@240V	31.7 A	40 A	31.7 A	40 A
Nominal Output Voltage L1-L2/L-N	240 Vac / 120 Vac	240 Vac / 120 Vac	240 Vac / 120 Vac	240 Vac / 120 Vac
Nominal Output Frequency	60 Hz	60 Hz	60 Hz	60 Hz
Output THDv (@Linear Load)	<3%	<3%	<3%	<3%
Inverter Battery Data				
Battery Voltage Range	80 - 495 V	80 - 495 V	80 - 495 V	80 - 495 V
Max. Charging/Discharging Current	50 A*	50 A*	50 A*	50 A*
System Battery Module Technical Data				
System Battery Module Model	SMILE-BAT-8.2PHA (With EMS)			
Chemistry	LFP (LiFePO4)	LFP (LiFePO4)	LFP (LiFePO4)	LFP (LiFePO4)
Nominal Capacity	8.2 kWh	8.2 kWh	8.2 kWh	8.2 kWh
Usable Capacity	7.8 kWh	7.8 kWh	7.8 kWh	7.8 kWh
Depth of Discharge (DoD)	95%	95%	95%	95%
Nominal Voltage	256 V	256 V	256 V	256 V
Voltage Range	236 ~ 288 V	236 ~ 288 V	236 ~ 288 V	236 ~ 288 V
Max. Charging/Discharging Current	38.4 A	38.4 A	38.4 A	38.4 A
Max. Charging/Discharging Power	7.6 kW	9.6 kW	7.6 kW	9.6 kW
Operating Temperature Range	-10°C ~ 50°C (14°F ~ 122°F) **			
Other Information	Inbuilt EMS	Inbuilt EMS	Inbuilt EMS	Inbuilt EMS

SMILE-SP/SPB SERIES



System Storage Capacity Extensions

Extension Battery Module Model	SMILE-BAT-8.2PHA			
Extension Battery Module Nominal	8.2 kWh	8.2 kWh	8.2 kWh	8.2 kWh
Extension Battery Module Usable	7.8 kWh	7.8 kWh	7.8 kWh	7.8 kWh
Max. Additional Battery Modules	5 Units	5 Units	5 Units	5 Units
Battery Modules Electrical Connection	Parallel	Parallel	Parallel	Parallel
Max. System Storage Capacity Nominal	49.2 kWh	49.2 kWh	49.2 kWh	49.2 kWh
Max. System Storage Capacity Usable	46.8 kWh	46.8 kWh	46.8 kWh	46.8 kWh

CT & Meter Data

Meter Type	AGF-AE-D/200			
Mounting	Din35 Rail			
Rated Voltage L-N	120 V			
Rated Voltage L1-L2	208 V / 240 V			
Rated RMS Current	200 A			
Current Measurement Accuracy	± 1%			
Number of Supplied Current Transformers	2			

General Data

Battery Charging/ Discharging to AC Max. Efficiency	96.6%	96.6%	96.6%	96.6%
Operating Altitude	4000 m (>3000 m derating)			
Noise	<45 dB	<45 dB	<45 dB	<45 dB
Cooling Method	Intelligent Fan	Intelligent Fan	Intelligent Fan	Intelligent Fan
Mounting	Wall Bracket	Wall Bracket	Wall Bracket	Wall Bracket
Safety	Cell		UL 1973 UL9540A	
	Battery Pack		UL 1973 UL9540A	
	Inverter		IEEE 1547	
	System		UL 9540 UL1741	
Transport	UN 38.3			
Emissions	FCC			
Ingress Rating	NEMA Type 4X			
Communication	WiFi			

* Need to configure more than two batteries

** When the ambient temperature is too low or too high, the performance of battery may be limited

SMILE-SP/SPB SERIES



Mechanical Specifications

Inverter	Battery Modules
16.3 in × 31.1 in × 6.9 in W×H×D (415 mm × 791 mm × 175 mm)	22.8 in × 31.3 in × 9.0 in W×H×D (580 mm × 800 mm × 230 mm)
32 kg (70.5 lbs)	81 kg (178.7 lbs)
Transformer	Meter Dimensions
13.6 in × 10.9 in × 6.8 in W×H×D (345 mm × 277 mm × 174 mm)	2.13 in × 3.65 in × 2.05 in W×H×D (54.1 mm × 92.6 mm × 52 mm)
22 kg (48.5 lbs)	0.2 kg (0.441 lbs)

* SMILE-SP Series 7.6kW System contains the following components: 7.6kW hybrid inverter + 8.2kWh battery module + Transformer + Meter

* SMILE-SP Series 9.6kW System contains the following components: 9.6kW hybrid inverter + 8.2kWh battery module + Transformer + Meter

Alpha ESS USA, Inc.
 ☎ +1 408 368 7828
 ✉ usa@alpha-ess.com
 📍 Unit 5, 2180 S Ivanhoe St, Denver, CO 80222

Alpha ESS Co., Ltd.
 ☎ +86 513 8060 6891
 ✉ info@alpha-ess.com
 🌐 www.alphaess.com
 📍 Jihua Road 888, Nantong High-Tech Industrial Development Zone, Nantong City, 226300

Alpha ESS Suzhou Co., Ltd.
 ☎ +86 512 6828 7609
 ✉ info@alpha-ess.com
 🌐 www.alphaess.com
 📍 Building 10-A, Canal Town Industrial Park, 99 Taihu E Rd, Wuzhong District, Suzhou 215000

Alpha ESS Australia Pty. Ltd.
 ☎ +61 402 500 520 (Sales)
 ☎ +61 1300 968 933 (Technical Support)
 ✉ info@alpha-ess.com
 🌐 www.alphaess.com

Alpha ESS Europe GmbH
 ☎ +49 610 3459 1601
 ✉ europe@alpha-ess.de
 🌐 www.alphaess.de
 📍 Paul-Ehrlich-Straße 1a, D-63225 Langen, Hessen

Alpha ESS Italy S.r.l.
 ☎ +39 339 462 4288
 ✉ info@alpha-ess.it
 🌐 www.alphaess.com
 📍 Via Don Minzoni, 17, Calenzano Firenze 50041

Alpha ESS Korea Co., Ltd.
 ✉ info@alpha-ess.com
 📍 2F, 19-4, Nohyeong 11-gil, Jeju-si, Jeju-do, Republic of Korea

Alpha ESS International Pte. Ltd.
 ☎ +65 6513 1125 / +65 6513 1126
 ✉ Singapore@alpha-ess.com
 📍 2 Corporation Road #01-06A Corporation Place Singapore 618494

Alpha ESS UK Ltd.
 ☎ +44 145 354 5222
 ✉ info@alpha-ess.com
 📍 Drake House, Long Street, Dursley, gl11 4hh